



**TO WHOMSOEVER IT MAY CONCERN**



**PE-25 Declaration-LLDPE F2001S**

OPaLene grade F2001S is a Butene Co-monomer based Linear Low Density Polyethylene (LLDPE) which can be used for Drip lateral applications. This grade contains medium slip and silica additives.

This grade meets the requirements of material as per IS 12786: 1989 (amendment No. 7) on 'Irrigation equipment-Polyethylene pipes for irrigation laterals specification'.

When incorporated with adequate quantity of carbon black as specified in clause 4.1 of IS 12786: 1989, the lateral pipe made from this grade will meet the creep rupture stress requirement of PE-25 class.

**This declaration of OPaL is restricted to the material as it leaves the OPaL facilities and does not include any substance subsequently added by the converter.**

**This is electronically generated document. Hence do not bear any signature.**

---

**ONGC Petro additions Limited (OPaL), Product Applications & Research Center (PARC), Plot No. Z/1 and Z/83, SEZ-1, Dahej Industrial Area, Dist. Bharuch, Gujarat 392130, India**

**Regd. Office: 35, Nutan Bharat Co-operative Housing Society Limited, R.C. Dutt Road, Akapuri, Vadodara-390007, Gujarat, India Telephone: +91-265-6192600 Fax: +91-265-6192622/666 Corporate Site: [www.opalindia.in](http://www.opalindia.in)**